



# Cisco

## 642-885 Exam

**Deploying Cisco Service Provider Advanced Routing  
(SPADVOUTE)**

**Thank you for Downloading 642-885 exam PDF Demo**

**You can Buy Latest 642-885 Full Version Download**

<https://www.certkillers.net/Exam/642-885>


<https://www.certkillers.net>

---

**Question: 1**

---

Referring to the topology diagram show in the exhibit,



Which three statements are correct regarding the BGP routing updates? (Choose three.)

- A. The EBGP routing updates received by R1 from R5 will be propagated to the R2, R4, and R7 routers
- B. The EBGP routing updates received by R3 from R6 will be propagated to the R2 and R4 routers
- C. The EBGP routing updates received by R1 from R5 will be propagated to the R2 and R4 routers
- D. The IBGP routing updates received by R3 from R2 will be propagated to the R6 router
- E. The IBGP routing updates received by R2 from R1 will be propagated to the R3 router
- F. The IBGP routing updates received by R1 from R4 will be propagated to the R5, R7, and R2 routers

---

**Answer: A, B, D**

---

---

**Question: 2**

---

When a BGP route reflector receives an IBGP update from a non-client IBGP peer, the route reflector will then forward the IBGP updates to which other router(s)?

- A. To the other clients only
- B. To the EBGP peers only
- C. To the EBGP peers and other clients only

D. To the EBGp peers and other clients and non-clients

---

**Answer: C**

---

---

**Question: 3**

---

Which two BGP mechanisms are used to prevent routing loops when using a design with redundant route reflectors? (Choose two.)

- A. Cluster-list
- B. AS-Path
- C. Originator ID
- D. Community
- E. Origin

---

**Answer: A, C**

---

---

**Question: 4**

---

Which two statements correctly describe the BGP ttl-security feature? (Choose two.)

- A. This feature protects the BGP processes from CPU utilization-based attacks from EBGp neighbors which can be multiple hops away
- B. This feature prevents IBGP sessions with non-directly connected IBGP neighbors
- C. This feature will cause the EBGp updates from the router to be sent using a TTL of 1
- D. This feature needs to be configured on each participating BGP router
- E. This feature is used together with the ebgp-multihop command

---

**Answer: A, D**

---

---

**Question: 5**

---

When implementing source-based remote-triggered black hole filtering, which two configurations are required on the edge routers that are not the signaling router? (Choose two.)

- A. A static route to a prefix that is not used in the network with a next hop set to the Null0 interface
- B. A static route pointing to the IP address of the attacker
- C. uRPF on all external facing interfaces at the edge routers
- D. Redistribution into BGP of the static route that points to the IP address of the attacker
- E. A route policy to set the redistributed static routes with the no-export BGP community

---

**Answer: A, C**


---

---

**Question: 6**

---

Refer to the topology diagram shown in the exhibit and the partial configurations shown below.



Once the attack from 209.165.201.144/28 to 209.165.202.128/28 has been detected, which additional configurations are required on the P1 IOS-XR router to implement source-based remote-triggered black hole filtering?

!

```

router bgp 123
address-family ipv4 unicast
redistribute static route-policy test
!

```

```

A. router static
address-family ipv4 unicast
209.165.202.128/28 null0 tag 666
192.0.2.1/32 null0 tag 667
!

```

```

route-policy test
if tag is 666 then
set next-hop 192.0.2.1
endif
if tag is 667 then
set community (no-export)
endif
end-policy
!

```

```

B. router static
address-family ipv4 unicast
209.165.201.144/28 null0 tag 666
192.0.2.1/32 null0 tag 667
!

```

```

route-policy test
if tag is 666 then
set next-hop 192.0.2.1
endif
if tag is 667 then

```

```
set community (no-export)
endif
end-policy
!
C. router static
address-family ipv4 unicast
209.165.201.144/28 null0 tag 666
192.0.2.1/32 null0
!
route-policy test
if tag is 666 then
set next-hop 192.0.2.1
set community (no-export)
endif
end-policy
D. router static
address-family ipv4 unicast
209.165.202.128/28 null0 tag 666
192.0.2.1/32 null0
!
route-policy test
if tag is 666 then
set next-hop 192.0.2.1
set community (no-export)
endif
end-policy
!
```

---

**Answer: C**

---

---

**Question: 7**

---

In Cisco IOS-XR, the maximum-prefix command, to control the number of prefixes that can be installed from a BGP neighbor, is configured under which configuration mode?

- A. RP/0/RSP0/CPU0:P2(config-bgp)#
- B. RP/0/RSP0/CPU0:P2(config-bgp-af)#
- C. RP/0/RSP0/CPU0:P2(config-bgp-nbr)#
- D. RP/0/RSP0/CPU0:P2(config-bgp-nbr-af)#

---

**Answer: D**

---

---

**Question: 8**

---

In Cisco IOS-XR, the ttl-security command is configured under which configuration mode?

- A. RP/0/RSP0/CPU0:P2(config)#

- B. RP/0/RSP0/CPU0:P2(config-bgp)#
- C. RP/0/RSP0/CPU0:P2(config-bgp-nbr)#
- D. RP/0/RSP0/CPU0:P2(config-bgp-af)#
- E. RP/0/RSP0/CPU0:P2(config-bgp-nbr-af)#

---

**Answer: C**

---

CertKillers.net

**Thank You for trying 642-885 PDF Demo**

To Buy Latest 642-885 Full Version Download visit link below

<https://www.certkillers.net/Exam/642-885>

**Start Your 642-885 Preparation**

**[Limited Time Offer]** Use Coupon “CKNET” for Further discount on your purchase. Test your 642-885 preparation with actual exam questions.

<https://www.certkillers.net>